INVERTER / ENPHASE

Enphase IQ8HC Microinverter

IQ8HC-72-M-US

IQ8HC converts DC power into AC at each solar panel. Each panel has its own inverter and monitoring, so you can see how individual panels are performing in the Enphase App.



380 VA	384 VA	25 years
Continuous AC output	Peak AC output	US warranty

For your home

Each panel works independently
A microinverter converts power at each panel rather than using one shared string inverter.

See individual panel performance
Panel-level monitoring helps show how your array is working and where attention is needed.

Your system

- Panel voltage and current limits
- Branch circuit layout and IQ Gateway
- Battery and backup controls, if included

MODEL DETAILS

Specifications & warranty

Enphase IQ8HC Microinverter · IQ8HC-72-M-US

Specification	Value
US model	IQ8HC-72-M-US
Common panel pairing range	320–540 W DC
MPPT voltage range	29.5–45 V
Maximum DC input voltage	60 V
Maximum continuous DC current	14 A
Maximum module short-circuit current	20 A
Continuous / peak output at 240 V	380 / 384 VA
CEC efficiency at 240 V	97.0%
Nominal grid frequency	60 Hz
Enclosure	NEMA Type 6
US warranty	25 years

Warranty

25-year limited manufacturer warranty in the United States.

Inverter output ratings are per unit. Enphase output values above are at 240 V.

Original sources

Enphase IQ8HC North American data sheet